


16 MB 11

AMPERE	16		32	
AANTAL POLEN	2	3	2	3
a	70,0	70,0	70,0	70,0
b	80,0	80,0	80,0	80,0
c	113,0	113,0	113,0	113,0
d	80,0	80,0	80,0	80,0
e	55,0	55,0	55,0	55,0
f	11,0	11,0	11,0	11,0
h	5,2	5,2	5,2	5,2
i	5,0	5,0	5,0	5,0
k	M 25	M 25	M 25	M 25
kabel mm ² min.	4	4	4	4
kabel mm ² max.	10	10	10	10

Wandcontactdoos

- Kabelinvoer eenmaal boven (open)
- Spatwaterdicht IP44




16 MB 13

AMPERE	16		32	
AANTAL POLEN	2	3	2	3
a	55,0	55,0	55,0	55,0
b	55,0	55,0	55,0	55,0
c	45,0	45,0	45,0	45,0
d	45,0	45,0	45,0	45,0
e	5,2	5,2	5,2	5,2
f	6,0	6,0	6,0	6,0
h	22,0	22,0	22,0	22,0
i	37,0	37,0	37,0	37,0
k	67,0	67,0	67,0	67,0
l	49,0	49,0	49,0	49,0
m	12,0	12,0	12,0	12,0
kabel mm ² min.	4	4	4	4
kabel mm ² max.	10	10	10	10

Inbouwcontactdoos

- Rech
- Flens 55 x 55 mm
- Spatwaterdicht IP44




16 MB 21

AMPERE	16		32	
AANTAL POLEN	2	3	2	3
a	70,0	70,0	70,0	70,0
b	70,0	70,0	70,0	70,0
c	56,5	56,5	56,5	56,5
d	56,5	56,5	56,5	56,5
e	5,5	5,5	5,5	5,5
f	8,0	8,0	8,0	8,0
h	22,0	22,0	22,0	22,0
i	37,0	37,0	37,0	37,0
k	67,0	67,0	67,0	67,0
l	49,0	49,0	49,0	49,0
m	4,0	4,0	4,0	4,0
kabel mm ² min.	4	4	4	4
kabel mm ² max.	10	10	10	10

Inbouwcontactdoos

- Rech
- Flens 70 x 70 mm
- Spatwaterdicht IP44




16 MB 13

AMPERE	16		32	
AANTAL POLEN	2	3	2	3
a	75,0	75,0	75,0	75,0
b	75,0	75,0	75,0	75,0
c	60,0	60,0	60,0	60,0
d	60,0	60,0	60,0	60,0
e	5,2	5,2	5,2	5,2
f	6,0	6,0	6,0	6,0
h	22,0	22,0	22,0	22,0
i	37,0	37,0	37,0	37,0
k	67,0	67,0	67,0	67,0
l	49,0	49,0	49,0	49,0
m	2,0	2,0	2,0	2,0
kabel mm ² min.	4	4	4	4
kabel mm ² max.	10	10	10	10

Inbouwcontactdoos

- Rech
- Flens 75 x 75 mm
- Spatwaterdicht IP44




16 MB 12

AMPERE	16		32	
AANTAL POLEN	2	3	2	3
a	68,0	68,0	68,0	68,0
b	62,0	62,0	62,0	62,0
c	53,0	53,0	53,0	53,0
d	47,0	47,0	47,0	47,0
e	5,2	5,2	5,2	5,2
f	6,0	6,0	6,0	6,0
h	36,0	36,0	36,0	36,0
i	35,0	35,0	35,0	35,0
alpha	20°	20°	20°	20°
n	56,0	56,0	56,0	56,0
m	52,0	52,0	52,0	52,0
kabel mm ² min.	4	4	4	4
kabel mm ² max.	10	10	10	10

Inbouwcontactdoos

- Hoek 20°
- Flens 68 x 62 mm
- Spatwaterdicht IP44



24V 50-60 Hz	42V 50-60 Hz	100-200 Hz bis 50V	300 Hz bis 50 V	400 Hz bis 50 V	≡ bis 50 V
-----------------	-----------------	--------------------------	--------------------	--------------------	---------------

Verp.
eenh. Gewicht
G/
stuk



Ampère	Aantal polen	24V 50-60 Hz	42V 50-60 Hz	100-200 Hz bis 50V	300 Hz bis 50 V	400 Hz bis 50 V	≡ bis 50 V	Verp. eenh.	Gewicht G/ stuk
16	2	41 0	41 1	41 2	41 3	41 4	41 5	10	200
16	3	41 6	41 7	41 8	41 9	41 10		10	220
32	2	41 11	41 12	41 13	41 14	41 15	41 16	10	205
32	3	41 17	41 18	41 19	41 20	41 21		10	220



Ampère	Aantal polen	24V 50-60 Hz	42V 50-60 Hz	100-200 Hz bis 50V	300 Hz bis 50 V	400 Hz bis 50 V	≡ bis 50 V	Verp. eenh.	Gewicht G/ stuk
16	2	43 0	43 1	43 2	43 3	43 4	43 5	10	130
16	3	43 6	43 7	43 8	43 9	43 10		10	150
32	2	43 11	43 12	43 13	43 14	43 15	43 16	10	130
32	3	43 17	43 18	43 19	43 20	43 21		10	150



Ampère	Aantal polen	24V 50-60 Hz	42V 50-60 Hz	100-200 Hz bis 50V	300 Hz bis 50 V	400 Hz bis 50 V	≡ bis 50 V	Verp. eenh.	Gewicht G/ stuk
16	2	43 22	43 23	43 24	43 25	43 26	43 27	10	150
16	3	43 28	43 29	43 30	43 31	43 32		10	170
32	2	43 33	43 34	43 35	43 36	43 37	43 38	10	150
32	3	43 39	43 40	43 41	43 42	43 43		10	170




Ampère	Aantal polen	24V 50-60 Hz	42V 50-60 Hz	100-200 Hz bis 50V	300 Hz bis 50 V	400 Hz bis 50 V	≡ bis 50 V	Verp. eenh.	Gewicht G/ stuk
16	2	43 54	43 55	43 56	43 57	43 58	43 59	10	155
16	3	43 60	43 61	43 62	43 63	43 64		10	170
32	2	43 65	43 66	43 67	43 68	43 69	43 70	10	155
32	3	43 71	43 72	43 73	43 74	43 75		10	170



Ampère	Aantal polen	24V 50-60 Hz	42V 50-60 Hz	100-200 Hz bis 50V	300 Hz bis 50 V	400 Hz bis 50 V	≡ bis 50 V	Verp. eenh.	Gewicht G/ stuk
16	2	42 0	42 1	42 2	42 3	42 4	42 5	10	140
16	3	42 6	42 7	42 8	42 9	42 10		10	160
32	2	42 11	42 12	42 13	42 14	42 15	42 16	10	140
32	3	42 17	42 18	42 19	42 20	42 21		10	160

LAAGSPANNINGS-STEKER, WANDTOESTELCONTACTDOOS/ KOPPELING


IEC 309, EN 60309, VDE 0623 beschermingsfactor IP44



AMPERE	16		32	
AANTAL POLEN	2	3	2	3
a	62,0	62,0	62,0	62,0
b	145,0	145,0	145,0	145,0
c	55,0	55,0	55,0	55,0
d Ø	7,0	7,0	7,0	7,0
e Ø	24,5	24,5	24,5	24,5
f	123,0	123,0	123,0	123,0
i	50,0	50,0	50,0	50,0
kabel mm ² min.	4	4	4	4
kabel mm ² max.	10	10	10	10

Steker


- Met tule
- Spatwaterdicht IP44



AMPERE	16		32	
AANTAL POLEN	2	3	2	3
a	62,0	62,0	62,0	62,0
b	129,0	129,0	129,0	129,0
c	55,0	55,0	55,0	55,0
d Ø	24,5	24,5	24,5	24,5
f	107,0	107,0	107,0	107,0
i	50,0	50,0	50,0	50,0
kabel mm ² min.	4	4	4	4
kabel mm ² max.	10	10	10	10

Steker


- Met wartel
- Spatwaterdicht IP44



AMPERE	16		32	
AANTAL POLEN	2	3	2	3
a	70,0	70,0	70,0	70,0
b	80,0	80,0	80,0	80,0
c	100,0	100,0	100,0	100,0
d	82,0	82,0	82,0	82,0
e	55,0	55,0	55,0	55,0
f	11,0	11,0	11,0	11,0
h Ø	5,2	5,2	5,2	5,2
i	5,0	5,0	5,0	5,0
k	M 25	M 25	M 25	M 25
kabel mm ² min.	4	4	4	4
kabel mm ² max.	10	10	10	10

Wandtoestelcontactstop


- Spatwaterdicht IP44



AMPERE	16		32	
AANTAL POLEN	4	5	4	5
a	62,0	62,0	62,0	62,0
b	158,0	158,0	158,0	158,0
c	67,0	67,0	67,0	67,0
d Ø	7,0	7,0	7,0	7,0
e Ø	24,5	24,5	24,5	24,5
kabel mm ² min.	4	4	4	4
kabel mm ² max.	10	10	10	10

Koppeling


- Met tule
- Spatwaterdicht IP44



AMPERE	16		32	
AANTAL POLEN	2	3	2	3
a	62,0	62,0	62,0	62,0
b	142,0	142,0	142,0	142,0
c	67,0	67,0	67,0	67,0
d Ø	24,5	24,5	24,5	24,5
kabel mm ² min.	4	4	4	4
kabel mm ² max.	10	10	10	10

Koppeling

- Met wartel
- Spatwaterdicht IP44



24V 50-60 Hz	42V 50-60 Hz	100-200 Hz bis 50V	300 Hz bis 50 V	400 Hz bis 50 V	≡ bis 50 V
-----------------	-----------------	--------------------------	--------------------	--------------------	---------------

Verp.
eenh. Gewicht

Ampère Aantal polen - 12h 4h 2h 3h 10h G/
stuk



16	2	44 0	44 1	44 2	44 3	44 4	44 5	10	140
16	3	44 6	44 7	44 8	44 9	44 10		10	160
32	2	44 11	44 12	44 13	44 14	44 15	44 16	10	140
32	3	44 17	44 18	44 19	44 20	44 21		10	160



16	2	44 22	44 23	44 24	44 25	44 26	44 27	10	150
16	3	44 28	44 29	44 30	44 31	44 32		10	170
32	2	44 33	44 34	44 35	44 36	44 37	44 38	10	150
32	3	44 39	44 40	44 41	44 42	44 43		10	170



16	2	46 0	46 1	46 2	46 3	46 4	46 5	10	160
16	3	46 6	46 7	46 8	46 9	46 10		10	170
32	2	46 11	46 12	46 13	46 14	46 15	46 16	10	160
32	3	46 17	46 18	46 19	46 20	46 21		10	170



16	2	45 0	45 1	45 2	45 3	45 4	45 5	10	185
16	3	45 6	45 7	45 8	45 9	45 10		10	205
32	2	45 11	45 12	45 13	45 14	45 15	45 16	10	185
32	3	45 17	45 18	45 19	45 20	45 21		10	205



16	2	45 22	45 23	45 24	45 25	45 26	45 27	10	190
16	3	45 28	45 29	45 30	45 31	45 32		10	210
32	2	45 33	45 34	45 35	45 36	45 37	45 38	10	190
32	3	45 39	45 40	45 41	45 42	45 43		10	210